IQ8MCP compact FM, small, red with isolator and glass pane



Features:

- · Slimline design
- · Low power consumption
- Plug-in connection terminals (two direction)
- · Optional terminal terminals
- Triple key function (test, open, reset)
- · Detectors that are not ready for operation can be marked with the "Out of order" label by reversing the enclosed glass pane

Part-No.: 804971.IN Approval: VdS, FM

Suitable for esserbus and powered loop connection, with soft address coding, alarm latch and alarm indicator. Conventional detectors can be connected to input of the MCP. Without BUS communication, the detector operates as conventional MCP. Detector housing is included. Built in isolators maintaining loop integrity.

Common technical data

8 ... 42 V DC Operating voltage Quiescent current @ 19 V DC 45 µA Alarm current w/o communication curtain

No. of detector/zone max. 127 detectors per loop (according to VdS)

Operation indicator

Alarm display red LED and yellow actuation indicator

max. 2.5 mm² (AWG 26-14) Connection terminal

Application temperature -20 °C ... 70 °C Storage temperature -30 °C ... 75 °C

IP 43, IP 55 with cover 704965 Type of protection

Housing PC ASA plastic Color red, similar to RAL 3020 Weight approx. 110 g

Detector specification EN 54-11, type A

W: 88 mm H: 88 mm D: 21 mm Dimensions

Declaration of Performance DoP-20492130701

If the glass pane is replaced with the optionally available plastic pane with reset function, the MCP can be reset from the outside using the key. For the surface mounting of the MCP the surface mount base Part No. 704980 must be ordered separately, if the cable wasn't laid about a standard flush mount wall socket. Type a definition - single action in accordance with EN 54-11 § 3.4.1 (excerpt taken from EN standard): Manual fire alarm unit, for which the alarm status is automatically set (additional alarm triggering is not required) after the fragile element has been broken or its position has been changed.



1 x glass pane, 1 x key, 1 x multilingual paper labels with "Out of order" pictogram

Accessories:

704980 Surface mount housing

Phone: +49 2131 40615 600

Faximile: +49 2131 40615 606