

# STI Universal Call Point Stopper Flush Mount with Sounder

Part No. **STI-13020FR**



## Overview

IP56 rated protective cover for flush mounted manual call points.

Suitable for indoor and outdoor use.

Helps prevent malicious activation by emitting a piercing 96dB alarm tone when its hinged cover is lifted.

Comprises a clear, tamper proof cover and frame that retrofits over all known break glass call points.

Ideal for schools, colleges, hospitals and other areas where there is a threat of false activation.

Kit includes one Universal Stopper frame, a red header labelled 'IN CASE OF FIRE - LIFT BREAK GLASS' and one break seal.

Surface and non-sounder variants also available (see variants tab below).

Main picture shows Universal Stopper with Manual Call Point. The call point is NOT supplied.

## Technical Specifications

Compatibility	Can be used with all known UK 'single gang' manual call points.
Power requirements	Sounder powered by a 3V lithium battery (supplied).
Onboard Sounder	Yes - 96dB @ 1 metre
Product dimensions (mm)	116 W x 138 H x 64 D mm.
Construction & finish	UV-stabilised polycarbonate.
IP Rating	IP56 (can be used indoors and outdoors)
Operating conditions/temperature	Polycarbonate tested -40°C (-40°F) to 49°C (120°F).



T 01942 322744    E sales@c-tec.co.uk  
F 01942 829867    W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom