

Optical smoke detector IQ8Quad FM with isolator



Part-No.: 802371.IN

Approval: VdS, BOSEC, FM

Optical smoke detector to guarantee safe and early detection of fire. Intelligent fire detector with decentralized intelligence, automatic function self-test, CPU failure mode, alarm and operating data memory, alarm indicator, soft-addressing and operating indication. The detector is provided with an integrated isolator. A parallel detector indicator can be connected.

Common technical data

Operating voltage $$8 \dots 42 \ V \ DC$$ Quiescent current @ 19 V DC $$50 \ \mu A$$

Quiescent current @ FACP battery approx. 200 μ A @ 27,5 V Quiescent current @ FACP battery approx. 280 μ A @ 42 V

Alarm current w/o communication curtain 18 mAArea to be monitored 110 m^2 Height to be monitored 12 m

Air velocity 0 m/s ... 25.4 m/s Application temperature -20 °C ... 72 °C Storage temperature -25 °C ... 75 °C Air humidity < 95 %

Type of protection IP 43 (incl. base + option)

Material PC / ABS

Color white, similar to RAL 9010

Weight approx. 110 g
Detector specification EN 54-7 / -17

Dimensions Ø: 117 mm H: 49 mm (62 mm incl. base)

Declaration of Performance DoP-20104130701



Special colors on demand.



Without detector base

Accessories:

767800 Mounting bracket

805590.IN Standard detector base for IQ8Quad FM
805591.IN Detector base with relay contact for IQ8Quad FM

Subject to change without notice! © 2020 Honeywell International Inc.