

DSPA 0.45-2 AND DSPA 0.90-2 AEROSOL GENERATORS



Properties

- **FEATURES:**
- Exceptional effective non-toxic fire extinguishing agent
- Uniquely easy to install and maintain
- Certified according to EN 15276-1, ISO 15779, UL 2775 and BRL K23001
- Approved by EPA for SNAP listing
- Ecologically safe and environmentally friendly (O.D.P.=0, G.W.P.=0)
- Very cost efficient
- Available with built-in thermocord and electrical activator

Description

Description DSPA 0.45-2 and DSPA 0.90-2 are developed for the protection of small compartments in industrial environments. Mounting by means of 2 magnets with 90N pulling force which can stand up to 3G vibration, therefore they are suitable for use in heavy industrial circumstances. DSPA 0.45-2 and DSPA 0.90-2 are available with electrical activation or thermal activation.

Application

The DSPA generators 0.45-2 and 0.90-2 are recommended for the protection of very small objects, such as small electrical equipment, airco's, ventilation, small electrical cabinets and computers. When calculating the volume, the dimensions of the present materials can be deducted.

Specifications

Model	0.45-2	0.90-2
Dimensions	Ø36 x 95 (x 90) 1.42 x 3.74 (x 3.54)	Ø36 x 150 (x 90) 1.42 x 5.905 (x 3.54)
Part number	100901 (e) / 100902 (t)	100903 (e) / 100904 (t)
Total weight	0.155 kg 0.342 lbs	0.285 kg 0.628 lbs
Compound weight	45 gr. / 0.01 lbs	90 gr. / 0.02 lbs
Volume coverage	0.44 m ³ 15.54 ft ³	0.88 m ³ 31.08 ft ³
Discharge time	27-28 sec.	53-57 sec.
Activation, current	Built-in starter, 1.3A (e) or built-in thermocord (t)	
Operation conditions	-40°C to 75°C / -40°F to 167°F Up to 95% RH	
Colour	Standard RAL 3000, other colours upon request	