

## VESDA-E VEU with LED's



### Features:

- Flair detection technology delivers reliable very early warning in a wide range of environments with minimal nuisance alarms
- Multi stage filtration and optical protection with clean air barriers ensures lifetime detection performance
- Four alarm levels and an ultra wide sensitivity range deliver optimum protection for the widest range of applications
- Intuitive LCD icon display provides instant status information for immediate response
- Flow fault thresholds per port accommodate varying airflow conditions
- Smart on-board filter retains dust count and remaining filter life for predictable maintenance
- Extensive event log (20,000 events) for event analysis and system diagnostics
- AutoLearn™ smoke and flow for reliable and rapid commissioning
- Referencing to accommodate external environmental conditions to minimise nuisance alarms
- Fully backward compatible with VLP and VESDAnet
- Remote monitoring with iVESDA for system review and proactive maintenance
- Ethernet for connectivity with Xtralis software for configuration, secondary monitoring and maintenance
- Industry first. Aspirating detector secondary monitoring and maintenance via WiFi
- USB for PC configuration, and firmware upgrade using a memory stick
- Two programmable GPIOs (1 monitored) for flexible remote control
- Field replaceable sub-assemblies enable faster service and maximum uptime

**Part-No.: VEU-A00**

**Approval: UL, ULC, VdS, CE, ActivFire**

The VEU series of aspirating smoke detectors are the premium detector of the VESDA-E range. An Ultra-wide sensitivity range; 15 times greater than VESDA VLP, and provision for more sampling holes provide an increased coverage in high airflow applications by at least 40%. Considerably longer linear pipe runs and extended branched pipe network configurations cater perfectly to applications with higher ceilings providing an increased coverage by up to 80% whilst allowing convenient detector mounting for ease of service and maintenance. A range of revolutionary new features provide unsurpassed detection performance, flexibility, field programmability, connectivity and reduced total cost of ownership. Flair Detection Technology

Flair is the revolutionary new detection chamber that forms the core of VESDA-E VEU, providing better detection, fewer nuisance alarms, higher stability, increased longevity and particle characterisation. Direct imaging of the sampled particles using a CMOS imager combined with multiple photo-diodes provides vastly more data that can be used to derive actionable information about the observed particles using analytics.

### Installation, Commissioning and Operation

VESDA-E VEU features a robust IP40-rated enclosure and is equipped with a powerful aspirator that provides a total pipe length of 800 m (2,624 ft). Out of box operation is made possible with AutoConfig which allows airflow normalisation and AutoLearn Smoke and Flow to be initiated from within the detector. VEU is fully supported by the ASPIRE and Xtralis VSC software applications which facilitate ease of pipe network design, system commissioning and maintenance.

### VESDAnet™

VESDA devices communicate on VESDAnet which provides a robust bi-directional communication network allowing continued redundant operation even during single point wiring failures. VESDAnet enables primary reporting, centralized configuration, control, maintenance and monitoring.

### Ethernet and WiFi connectivity

VESDA-E detectors offer Ethernet and WiFi connectivity as standard features. The detector can be added to a corporate network, allowing WiFi enabled tablet devices and laptops installed with Xtralis configuration software to connect wirelessly to the detector via the network. Backward Compatibility

VESDA-E VEU is fully compatible with existing VESDA installations. The detector occupies the same mounting footprint, pipe, conduit and electrical connector positioning as VESDA VLP. VEU is also compatible with existing VESDAnet installations allowing monitoring of both VESDA-E and legacy detectors via the latest iVESDA application

Operating voltage	18 ... 30 V DC
Quiescent current @ 24 V DC	approx. 613 mA
Alarm current @ 24 V DC	approx. 646 mA
Contact load relay	2 A @ 30 V DC NO/NC
Sensitivity	0.001% - 20% obs/m (0.0003% - 6.25% obs/ft)
Connection terminal	0.2 - 2.5 mm <sup>2</sup>
Maximum tube length	100 m
Area to be monitored	1600 m <sup>2</sup>
Type of protection	IP 40
Weight	approx. 4.83 kg
Specification	EN 54-20, Class A (80 holes / Fire 1 = 0.015% obs/m), Class B (80 holes / Fire 1 = 0.026% obs/m), Class C (100 holes / Fire 1 = 0.062% obs/m)
Dimensions	W: 350 mm H: 225 mm D: 135 mm



Internal filter included in detector

### Accessories:

VSP-962

VESDA filter for VEU, VEP