

SYNCRO SI

Analogue Addressable Extinguishant Status Indicators

Features

- ▶ Reduced installation costs
- ▶ Loop powered & wired directly onto either detection loop
- ▶ Optional mode select keyswitch
- ▶ Protected dual action manual release switch option
- ▶ Robust, high quality enclosure
- ▶ Only compatible with Apollo protocol Syncro XT and Syncro XT+ control Panels
- ▶ Weatherproof version available



Description

Designed specifically for Syncro XT and Syncro XT+ extinguishing control panels, the Sigma Si system status indicator provides indication and control at any entrance to a protected area.

Syncro Si status indicators are “addressable” and loop powered and are designed to be connected to the detection loop of Syncro XT or Syncro XT+ extinguishing control panels, offering the installer significant savings in installation time.

Specification

Construction	1.2mm mild sheet steel
IP rating (standard unit)	IP30
IP rating (weatherproof unit)	IP65
Colour - lid & box	BS 00 A 05 grey - fine texture
Weight	1kg
Protocol	Apollo
Quiescent current	0.02A
Cable capacity	2.5mm ² per terminal
Inputs trigger threshold	700 ohms to 100 ohms

Equipment		
Product Code	Description	Size
A91000M8	Syncro Si status unit surface	190 x 136 x 50
A91100M8	Syncro Si status unit c/w Manual Release surface	190 x 136 x 50
A91110M8	Syncro Si status unit c/w Manual Release & Mode Select surface	190 x 136 x 50
A91000W8	IP65 - Syncro Si status unit	265 X 170 X 60
A91100W8	IP65 - Syncro Si status unit c/w Manual Release	265 X 170 X 60
A91110W8	IP65 - Syncro Si status unit c/w Manual Release & Mode Select	265 X 170 X 60
A90001M10	Syncro Si extinguishant hold off switch unit	97 x 97 x 50