

# CDXconventional

## CCP-W

### CONVENTIONAL WEATHERPROOF MANUAL CALL POINT

#### Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Other colours available on request
- ▶ Ingress Protection rated to IP67
- ▶ Approved by LPCB.



#### Description

The CCP-W is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element and features a weatherproof Housing to IP67, which means it can be mounted in the most severe environmental conditions without water ingress.

#### Specification

Ordering codes	CCP-W CCP-W/Y
Nominal operating resistance	470 $\Omega$
Maximum contact resistance	200 $\Omega$
Ingress Protection Rating	IP67
Operating Temperature Range	-25 °C to + 70 °C
Storage Temperature Range	-25 °C to + 70 °C
Maximum Humidity	95%RH - Non condensing (at 40 °C)
Colour / Case Material	Red or Yellow / ABS
Weight (g) / Dimensions (mm)	234 / W98 x H94 x D78
Accessories	Frangible Element KAC/G/HE Non-Frangible Element KAC/EWS/HE