



**FW-MPS-1T-KL**



**FW-MPS-1T-LPA**

The Fire Watch manual pull station is a high quality non toxic die-cast manual pull station. Low profile design and smooth edges offer an attractive yet functional design. All components are powder coated or have plated surfaces to inhibit corrosion. A Single-Pole Single-Throw (SPST) switch rated for 10 amps @ 125 VAC provides consistent and reliable operation.

### **Standard Features**

- Rugged Die-Cast Design
- Single-Gang Mounting
- 14 GA Plated Steel Backplate
- Single- and Dual-Action (Lift and Pull) Models
- Operating Temperature: -40°F to 150°F, 85% RH
- 14 to 22 AWG Wiring Terminals
- Manufactured in the USA



UL Listed  
UNIU.S36878



## Ordering Information

Model	Description
FW-MPS-1T-KL	Manual Pull Station with Key Lock. SPST with Terminal Block, Red.
FW-MPS-1T-LPA	Manual Pull Station with Lift and Pull Cover. SPST with Terminal Block, Red.

## Specifications

### FW-MPS-1T-KL

Width	3.200"
Length	4.750"
Depth	0.875"
Weight	15.5 oz. / 420 grams
Switch Rating	10 amps @ 125 VAC

### FW-MPS-1T-LPA

Width	3.325"
Length	4.750"
Depth	1.500"
Weight	1lb. 4 oz. / 560 grams
Switch Rating	10 amps @ 125 VAC

*Fire Watch* is an American company based in California, USA. We supply fire protection and life-safety equipment solutions to the international market. We have a team of highly-qualified engineers on-staff to support you with all aspects of your project, including system design, product training, technical support, and after-sales support.

*These specifications are subject to change without notice.*

*For the latest product specifications visit our website at [www.fire-watch.co](http://www.fire-watch.co).*