


# CDXconventional

# CCP-SAVWIRE

## CONVENTIONAL MANUAL CALL POINT

### Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm<sup>2</sup> solid conductor
- ▶ Designed for use on “Savwire” (two-wire) systems



### Description

The CCP-SAVWIRE is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals. The unit has been specifically designed for use on “Savwire” (two-wire) systems.

The unit can support either a ‘Frangible Glass’ element or a ‘Non Frangible Plastic’ element.

## Specification

Ordering Code	CCP-SAVWIRE
Nominal operating resistance	470 Ω
Maximum contact resistance (R)	200 Ω
Ingress Protection Rating	IP24D
Operating Temperature Range	-20 °C to +55 °C
Storage Temperature Range	-20 °C to +55 °C
Maximum Humidity	95%RH - Non condensing (at 40 °C)
Colour / Case Material	Red / ABS
Weight (g) / Dimensions (mm)	(Flush Mount) 110 / W89 x H93 x D27.5 (Surface Mount with Back Box) 160 / W89 x H93 x D59.5
Accessories	Frangible Element KAC/G/HE Non-Frangible Element KAC/EWS/HE