QUICK ROLL

REF.NO. 2D663





Innovative handle ascender with integrated pulley, that can be used in the following applica-tions:

- Caving. Used in conjunction with a chest ascender (e.g. <u>CHEST ASCENDER+</u>), it allows for rope ascent with MAO technique (Fig A).
- Rope work. Used in conjunction with a self-braking descender (e.g. <u>SPARROW</u>) it allows for ascending the work rope. Ideal for placing protection and for rock scaling on crags (Fig B).

Main characteristics:

- overmolded, ergonomic handle ascender, designed for greater efficiency when pulling and increased resistence to wear and tear;
- cam opening lever usable with one hand; patented system for unlocking the cam, with just one downwards movement necessary;
- steel cam, manufactured with technology that implements the resistance to wear and tear. Equipped with a set of teeth that
 protects the wear of the rope, but it is equally effective in blocking and ascending the rope. It also has three slots to prevent the
 accumulation of mud and reduce the effort needed to slide the device up the rope under any condition (muddy rope, frozen
 etc.);
- two attachment holes for various possible uses, anti-inversion cam system, secondary hole for connecting a quick link for an etrier.

Attention! The integrated pulley is not PPE and it can only be used as an additional aid to the ascent, as per the methods shown, but not for hauling people and/or material.



grey (2D663SJ)



REF.NO. 2D663



orange (2D663DJ)


TECHNICAL FEATURES

Sizes 189 x 93 mm

Maximum load 140 kg



STANDARD AND ADDITIONAL INFORMATION



TABLES

Ref. No.	Handle	Colour
2D663SJ	left	grey
2D663DJ	right	orange

GALLERY

QUICK ROLL

REF.NO. 2D663













