

# Crowcon F-Gas Detector

## Fixed Point Gas Detectors



- Long-life IR sensor
- Highly reliable
- Low maintenance costs



# F-Gas Detector

## Refrigerant Gas and SF<sub>6</sub> Detector

**When lives and property are at risk and you need gas detection equipment that is totally reliable, you need Crowcon. For over 40 years Crowcon has been developing and manufacturing high quality products with a reputation for reliability and technical innovation.**

**Crowcon fixed detectors have been proven in many arduous environments, including oil and gas exploration, water treatment, steel and chemical plants. The Crowcon F-Gas detector provides dependable detection of refrigerant gases and sulphur hexafluoride in plant-room or switchgear applications.**



### Choosing the fixed gas detector for your needs

The Crowcon F-Gas detector is a high quality infrared (IR) fixed-point detector that delivers dependable detection of freon gases. Available for detecting a range of different refrigerant gases and also sulphur hexafluoride (SF<sub>6</sub>), the Crowcon F-Gas detector can be connected to any control system that accepts an analogue signal.

The Crowcon F-Gas detector utilises a high quality IR sensor specifically calibrated to detect the F-Gases commonly in use. The F-Gas detector operates from 24Vdc and provides a 4-20mA signal (the output can also be set to 0-20mA, 0-2V, 0-5V or 0-10Vdc).

Housed within an IP54 rugged enclosure, the F-Gas detector is suitable for use in non-hazardous areas such as plant rooms or switchgear rooms.

In addition to protecting personnel from toxic gas risks, installing the F-Gas detector also helps to reduce the risk of leakage of powerful 'greenhouse gases' into the environment.



## Accurate and reliable

Superior IR sensor technology	Provides fast, stable and dependable performance with low maintenance and long life. Unlike cheaper semi-conductor type sensors the F-Gas detector is not affected by other types of gas or changes in temperature or humidity.
-------------------------------	---

## Simple and versatile

LED indicators	Tri-coloured LED's indicate the operating status of the detector, and in combination with the function keys, facilitate simple adjustments such as zero and calibration.
Choice of output signals	The analogue output signal can be set as 4-20mA, 0-20mA, 0-2V, 0-5V or 0-10Vdc for compatibility with virtually any control system.

## Long life with low maintenance costs

No consumable parts	Provides many years of service with no requirement to replace the sensor or any other components.
Simple to test	Requires a bi-annual gas check only. Re-calibration is only necessary if readings are out of range.
IP54 rated enclosure	Provides good protection from dust and water ingress in indoor environments.

## Safety and compliance

F-Gas regulations compatible	Enables F-Gas suppliers and users to comply with the mandatory European F-Gas regulations.
Rapid gas leak detection	Provides an early warning that gas is leaking and thus maintains system efficiency and reduces expensive gas replacement costs.
Environmental protection	Helps to reduce the risk of leakage of powerful 'greenhouse gases' into the environment.

## F-Gas detector accessories



### Calibration adaptor

Enables calibration gas to be applied to the sensor.



### Calibration gas and regulators

Freon gases and SF<sub>6</sub> are available to enable sensor checking and calibration.

Please see the back page for full technical specifications.

## F-Gas detector specifications:

<b>Size</b>	151 x 80 x 60mm (5.9 x 3.1 x 2.4ins) (Total size with cable gland: 151mm x 102mm x 60mm)
<b>Weight</b>	0.25kg (8.8oz)
<b>Ingress protection</b>	IP54
<b>Measuring principle</b>	Non-dispersive infrared (NDIR)
<b>Range</b>	0-1000ppm
<b>Resolution</b>	1ppm
<b>Power</b>	12-28Vdc
<b>Analogue output</b>	4-20mA current source (can be set to 0-20mA, 0-2V, 0-5V or 0-10V)
<b>Operating temperature</b>	-20 to +40°C
<b>Humidity</b>	0-95% RH non-condensing
<b>Repeatability</b>	+/- 1% FSD
<b>Linearity</b>	+/- 2% FSD
<b>Start up time</b>	<120 seconds
<b>Response time</b>	30 seconds approximately
<b>Pressure</b>	800-1200mBar
<b>Approvals</b>	EMC: EN50270

This product is designed for non-hazardous area operation only.

## Refrigerant gas options:

### Pure fluids:

Fluids	Formula	Name	Measuring Range
<b>HCFC 22 (R22)</b>	CHClF <sub>2</sub>	Chlorodifluoromethane	1000ppm
<b>HCFC 123 (R123)</b>	CHCl <sub>2</sub> CF <sub>3</sub>	2,2-Dichloro-1,1,1-trifluoroethane	1000ppm
<b>HFC 125 (R125)</b>	C <sub>2</sub> HF <sub>5</sub>	Pentafluoroethane	1000ppm
<b>HFC 134a (R134a)</b>	CH <sub>2</sub> FCF <sub>3</sub>	1,1,1,2-Tetrafluoroethane	1000ppm

### Blended fluids used in refrigeration/ air conditioning market:

Refrigerant	Components	Measuring Range
<b>R404a</b>	R143a/125/134a	1000ppm
<b>R407a</b>	R32/125/134a	1000ppm
<b>R407c</b>	R32/125/134a	1000ppm
<b>R410a</b>	R32/125	1000ppm
<b>R507</b>	R143a/125	1000ppm

### Speciality fluid used for vehicle refrigeration:

Fluid	Formula	Name	Measuring Range
<b>R1234yf</b>	CH <sub>2</sub> =CFCF <sub>3</sub>	Tetrafluoropropene	1000ppm

### Insulating gas:

Gas	Name	Measuring Range
<b>SF<sub>6</sub></b>	Sulphur hexafluoride	1000ppm

Crowcon reserves the right to change the design or specification of the product without notice. Please check [www.crowcon.com](http://www.crowcon.com) for updates.

[www.crowcon.com](http://www.crowcon.com)

#### UK:

Tel: +44 (0) 1235 557700  
 Fax: +44 (0) 1235 557718  
 Email: [sales@crowcon.com](mailto:sales@crowcon.com)

#### US:

Tel: +1 859 957 1039  
 Toll Free: 800-527-6926  
 Fax: +1 513 957-1044  
 Email: [salesusa@crowcon.us](mailto:salesusa@crowcon.us)

#### NL:

Tel: +31 10 421 1232  
 Fax: +31 10 421 0542  
 Email: [eu@crowcon.com](mailto:eu@crowcon.com)

#### SG:

Tel: +65 6745 2936  
 Fax: +65 6745 0467  
 Email: [sales@crowcon.com.sg](mailto:sales@crowcon.com.sg)

#### CN:

Tel: +86 (0) 10 6787 0335  
 Fax: +86 (0) 10 6787 4879  
 Email: [saleschina@crowcon.com](mailto:saleschina@crowcon.com)

#### IN:

Tel: +91 22 6708 0400  
 Fax: +91 22 6708 0405  
 Email: [salesindia@crowcon.com](mailto:salesindia@crowcon.com)