



Highly Advanced Sensor & Optics

IR3 Flame Detector RFD-3000X

SPECIFICATION	
<u>General</u>	
Spectral Response	Triple IR Bands
Detection Range	200ft(60m) for n-Heptane fire
Field of View	Horizontal 90° Vertical 90°
Response Characteristics	Typical 5 seconds
Temperature Range	Operating : -40°C to +75°C. Storage : -50°C to +80°C.
Humidity Range	0 to 95% relative humidity
<u>Electrical</u>	
Operating Voltage	Typical DC24V (18 to 30)
Power Consumption	4.8W maximum at 30 vdc
Wiring	14AWG(2.08mm ²) to 24AWG(0.205mm ²) shielded cable recommended.
Electromagnetic Compatibility	EMC Protected
<u>OutPut</u>	
Relays	Fire Alarm: - Form A or B Selectable - Normally de-energized - Latching/Non-latching. - Contacts rated 2A at 28 vdc. Fault Alarm - From A - Normally Energized - Contacts rated 2A at 28 vdc. Warning Alarm : - From A - Normally De Energized - Contacts rated 2A at 28 vdc.

SPECIFICATION	
<u>OutPut</u>	
4-20mA	A maximum loop resistance of 400 ohms
	General Fault : 0mA +0.5mA Self Test Fault : 2mA ±0.5mA Normal : 4mA ±0.5mA Warning : 16mA ±0.5mA Alarm : 20mA ±0.5mA
RS-485	Proprietary communication
<u>Mechanical</u>	
Dimensions	W134 x H117 x D110 mm W5.3 x H6.41 x D4.3 Inch
Enclosure Material	Stainless steel 316
Shipping Weight	3.5 kg
Color	Metal
Conduit Entry Size	2 x 1/2 inch PF.
<u>Approvals</u>	
Performance Certification	FM3260
Hazardous area	Class I Division 1 Groups B,C and D Class II Division 1 Groups E,F and G Class III ATEX, IECEx, Ex d IIB+H2 T5
Explosion proof	IP66
Water and dust tight	
<u>Accessories</u>	
Fire Simulator Bracket	TL 305 BK-2



Highly Advanced Sensor & Optics

IR3 Flame Detector RFD-3000X

APPLICATION

Oil&Gas Plant



General Application



APPLICATION

Accessories



<Sun shield>



<Test Lamp_TL-305>



<Air shield>



<Bracket_BK-2>

False Alarm Immunity Tech

