

EVA50SS / EVC50SS MINI LED

zone 1

zone 2

Ex db IIC Gb Ex tb IIIC Db II2GD

T6
T 85°C

zone 21

zone 22

DIRECTIVE 2014/34/UE

LIGHTING FIXTURE LAMP
LED FLASH or FIXSEGNALATORE LUMINOSO LAMPADA
LED FLASH o FISSA

IP66




Caratteristiche:	Segnalatore luminoso con lampada LED (FLASH o FISSA) ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiere, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalampada L, N, Pe. Sez. max. 4mm2.
Features:	Lighting fixtures with long-life LED (FLASH or FIX), are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.
Materiali:	Corpo STAINLESS STEEL 316 , viteria in stainless steel, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).
Materials:	Body STAINLESS STEEL 316 , stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).



Stainless Steel 316

EVA50SS/FLASH

EVC50SS/FLASH



Specifica tecnica / Technical specification				
Modello / Type	EVA50SS/ML EVC50SS/ML	EVC50SS/ML EVC50SS/ML	EVA50SS/ML EVC50SS/ML	
Tensione / Voltage	12-24 VAC/DC	48 VAC	48 VDC	98 - 264 VAC/DC
Corrente / Rated current	200mA		200mA	
Temperatura / Working temperature	-20°C +60°C			
Frequenza / Frequency	50/60HZ			
Assorbimento medio / Power middle	2W			
Lamp power / Effective Intensity	6J			
Flash-minuto / Flash-minut	75 (other to be defined)			
Servizio / Service	Continuo / Continuous			
Colore corpo / Color body	Stainless steel natural / Other color on request			
Imbocchi / Cable entries	EVA50 1 x M25x1,5 - EVC50 2 x M25x1,5			



COLORI GEMME: **ROSSO - GIALLO - ARANCIO - VERDE - BLU - BIANCO**
Signaling lamps: **Red - yellow - orange - green - blue - white**



Kroma mec S.r.l.

47 LED SS

