

EVA50SS/FLASH EVC50SS/FLASH

zone 1

zone 2

Ex db IIC Gb Ex tb IIIC Db II2GD

T6
T 85°C

zone 21

zone 22

DIRECTIVE 2014/34/UE

LIGHTING FIXTURE
XENON FLASHING LAMPSEGNALATORE LUMINOSO
LAMPADA XENON

IP66



Stainless Steel 316

Caratteristiche: Segnalatore luminoso con lampada allo Xenon ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiere, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalamppada L, N, Pe. Sez. max. 4mm2.

Features: Lighting fixtures with long-life xenon bulb, are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for waterproof protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.

Materiali: Corpo **STAINLESS STEEL 316**, viteria in stainless steel, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).

Materials: Body **STAINLESS STEEL 316**, stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).



EVA50SS+KIT/FLASH

Specifica tecnica / Technical specification

| Modello / Type | EVA50SS EVC50SS | | SOLO EVC50SS ONLY EVC50SS | | EVA50SS EVC50SS | | |
|-----------------------------------|--|--------|------------------------------|---------|--------------------|---------|--|
| | 12-24 VAC/DC | 48 VAC | 48 VDC | 110 VAC | 110 VDC | 230 VAC | |
| Tensione / Voltage | 12-24 VAC/DC | 48 VAC | 48 VDC | 110 VAC | 110 VDC | 230 VAC | |
| Corrente / Rated current | 300mA | | | 40mA | | 20mA | |
| Temperatura / Working temperature | -20°C +60°C | | | | | | |
| Frequenza / Frequency | 50/60HZ | | | | | | |
| Assorbimento medio / Power middle | 2W | | | 1,8W | | 4,5W | |
| Lamp power / Effective Intensity | 6J 29Cd | | | | | | |
| Flash-minuto / Flash-minut | 75 (other to be defined) | | | | | | |
| Servizio / Service | Continuo / Continuous | | | | | | |
| Colore corpo / Color body | Stainless steel natural / Other color on request | | | | | | |
| Imbocchi / Cable entries | EVA50 1 x M25x1,5 - EVC50 2 x M25x1,5 | | | | | | |

EVA50SS/FLASH

EVC50SS/FLASH



COLORI GEMME: **ROSSO - GIALLO - ARANCIO - VERDE - BLU - BIANCO**
Signaling lamps: **Red - yellow - orange - green - blue - white**

