

EVA50/FLASH 21J EVC50/FLASH 21J

zone 1

zone 2

Ex d IIC Gb Ex tb IIIC Db II2GD

T6
T 85°C

-20°C

zone 21

zone 22

DIRECTIVE 2014/34/UE

+60°C

 LIGHTING FIXTURE
XENON FLASHING LAMP 21J

 SEGNALATORE LUMINOSO
LAMPADA XENON 21J

IP66



Intensità luminosa
Effective Intensity
21J 350Cd

Caratteristiche:	Segnalatore luminoso con lampada allo Xenon 21J ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiere, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalampana L, N, Pe. Sez. max. 4mm2.
Features:	Lighting fixtures with long-life xenon bulb 21J , are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.
Materiali:	Lega di alluminio a basso contenuto di rame, viteria in acciaio inox, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).
Materials:	Low copper content aluminium alloy, stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).

EVA50/FLASH

EVC50/FLASH

EVA50+KIT/FLASH



Specifica tecnica / Technical specification

	EVA50-21J EVC50-21J					
Tensione / Voltage	12-24 VAC/VDC	48 VAC	48 VDC	110 VAC	110VDC	230 VAC
Corrente / Rated current	350mA		100mA		25mA	
Temperatura / Working temperature	-20°C +60°C					
Frequenza / Frequency	40/60HZ					
Assorbimento medio / Power middle	20W~					
Lamp power / Effective Intensity	21J 350Cd					
Flash-minuto / Flash-minut	30 (other to be defined)					
Servizio / Service	Continuo / Continuous					
Colore corpo / Color body	RED RAL 3000 / Other color on request					
Imbocchi / Cable entries	EVA50 1 x 3/4" - EVC50 2 x 3/4"					



COLORI GEMME: **ROSSO - GIALLO - ARANCIO - VERDE - BLU - BIANCO**
Signaling lamps: **Red - yellow - orange - green - blue - white**

