

L100-L80-L60-L40 Stainless steel

zone 1

zone 2

Ex db IIC Gb II2GD



zone 21

zone 22

Ex tb IIIC Db II2GD

IP66



LIGHTING FIXTURE **LED**
EVA50SS-L - EVC50SS-L

SEGNALATORE LUMINOSO **LED**
EVA50SS-L - EVC50SS-L

T6

T 85°C



Prodotti LED Stainless Steel 316



Caratteristiche: Segnalatore luminoso con lampada **LED** ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiera, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalampada L, N, Pe. Sez. max. 4mm2.

Features: Lighting fixtures with long-life **LED**, are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for waterproof protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.

Materiali: Corpo STAINLESS STEEL 316, viteria in Stainless steel, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).

Materials: Body STAINLESS STEEL 316, stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).

EVC50SS-L



COLORI LED - COLOR LED	POTENZA - POWER	40 LED	60 LED	80 LED	100 LED
Rosso / Red	7 cd = 1 led	280 cd	420 cd	560 cd	700 cd
Giallo / Yellow	7 cd = 1 led	280 cd	420 cd	560 cd	700 cd
Verde / Green	20 cd = 1 led	800 cd	1200 cd	1600 cd	2000 cd
Blu / Blue	10 cd = 1 led	400 cd	600 cd	800 cd	1000 cd
Bianco / White	10 cd = 1 led	400 cd	600 cd	800 cd	1000 cd
Arancione / Orange	7 cd = 1 led	280 cd	420 cd	560 cd	700 cd

EVA50SS-L

5W L-40:
QTY LED 407W L-60:
QTY LED 608W L-80:
QTY LED 808W L-80:
QTY LED 80

Specifica tecnica / Technical specification

	EVA50SS-L EVC50SS-L	EVA50SS-L EVC50SS-L	EVA50SS-L EVC50SS-L
Tensione / Voltage	12-24 VAC/VDC	48 VAC	48 VDC
Corrente / Rated current	L-40 0,200mA - L-60 0,290mA - L-80 0,330mA - L-100 0,400mA a 24Vac/dc		
Frequenza / Frequency	50/60HZ		
Assorbimento medio / Power middle	(L-40 5W) - (L-60 7W) - (L-80 8W) - (L-100 10W)		
Potenza luminosa / Light Power	Vedere tabella - See Table		
Funzionamento da definire in ordine Working to be defined on order	FISSO oppure INTERMITTENTE oppure ROTANTE FIXED or INTERMITTENT or ROTATING		
Colore corpo / Color body	RED RAL 3000 Other color on request / Altri colori a richiesta		
Colore LED / LED Color	BIANCO - BLU - GIALLO - ROSSO - VERDE - ARANCIONE WHITE - BLUE - YELLOW - RED - GREEN - ORANGE		
Imbocchi / Cable entries	EVA50L 1 x M25 - EVC50L 2 x M25		

