

GNE_xCP6-BG Break Glass Manual Call Point

The flameproof GNE_xCP6-BG break glass manual call points are approved for Zone 1, 2, 21 and 22 hazardous areas for the control of fire and gas alarm systems. The robust, lightweight GRP enclosure is UV stable and provides a corrosion free initiation solution for harsh and hazardous applications on and offshore.

Available with optional EOL or series resistors, diode or Zener diodes and an LED indicator. Also with either single or double pole change over switches. Certified to IECEx and ATEX standards with additional PESO, INMETRO and Ex EAC approvals. The break glass element features a safety membrane and is designed to snap ensuring the no glass fragments are released during activation. A hammer is available as an accessory if required by local code.

Features

- Alternative housing colours are available to meet specific requirements
- Single or double pole c/o switch
- DIN rail mounted terminal blocks: 8 × 2.5mm²
- Metalised polyester or stainless steel “Duty” label
- Series and/or End of Line resistors, diodes & Zener diodes
- Optional Indicator LED
- Break glass hammer accessory available

Approvals

- ATEX certificate: Sira 09ATEX3286X
- IECEx certificate: IECEx SIR 09.0121X
- SIL 2 certified to IEC 61508 (2010)
- Ex EAC certified: KZ.1510019.22.01.00271
- PESO CCOE certified: P471504
- INMETRO certificate: IEx_10.0011X

Coding

- GNE_xCP6A-BG:
II 2G Ex db eb IIC T6 Gb Ta = -40°C to +75°C
II 2D Ex tb IIIC T75°C Db IP66
- GNE_xCP6B-BG:
II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +50°C
II 2D Ex tb IIIC T80°C Db IP66
- GNE_xCP6C-BG:
II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +65°C
II 2D Ex tb IIIC T75°C Db IP66



Specification

GNExCPA-BG:	A version
Coding:	II 2G Ex db eb IIC T6 Gb Ta = -40°C to +75°C II 2D Ex tb IIIC T75°C Db IP66
Switch rating:	250V ac Max. 5.0A 75V: Max 0.75A 50V: Max 1.0A 30V: 5.0A Max Resistive load 3.0A Inductive load 12V: Max 5.0A
GNExCPB-BG:	B version
Coding:	II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +50°C II 2D Ex tb IIIC T80°C Db IP66
Switch rating:	<50V: 1.0A >50V: 0.75A 56V dc Max.
Min. resistor (2W):	48V = 1K8 24V = 470R 12V = 120R 6V = 47R
LED	Optional LED indicator assembly
GNExCPC-BG:	C version
Coding:	II 2G Ex db eb mb IIC T4 Gb Ta = -40°C to +65°C II 2D Ex tb IIIC T75°C Db IP66
Switch rating:	<50V: 1.0A >50V: 0.75A 56V dc Max.
Min. resistor (1.75W):	48V = 2K 24V = 510R 12V = 150R 6V = 51R
General:	
Ambient:	Ta = -40°C to +75°C [-40° to +167°F] (+50°C for BExCP3B, +65°C for BExCP3C)
Ingress protection:	IP66
Enclosure material:	GRP - Glass Reinforced Polyester
Colour:	RAL3000 Red (others available on request)
Cable entries:	2 x M20 clearance top and 1 x M20 clearance side. Back box can be rotated to give 2 x bottom and 1 x side entries Adapters available to 1/2"NPT, 3/4"NPT or M25
Stopping plugs:	2 x Ex e nylon plugs as standard Brass, nickel plated brass and stainless steel Ex d plugs optional
Terminals:	6 × 4.0mm ² cables or or 8 × 2.5mm ² DIN rail
Test:	Test key facility
Weight:	1.2Kg/2.64lbs

Part Codes

Version:	Part reference:	Description:
Type:	GNExCP6ABG GNExCP6BBG GNExCP6CBG	Type A: no end of line devices Ta -40°C to +75°C Type B: end of line devices Ta -40°C to +50°C Type C: end of line devices Ta -40°C to +65°C
Switch Type: [s]	S D	SPCO/SPDT DPCO/DPDT
Terminals: [t]	D S	DIN Rail 8 × SAK2.5 6 × 4mm ² terminals
Lift flap: [l]	L N	Lift flap No lift flap
Cable Entry Type: [e]	A B C D E F G	3 x M20x1.5mm 2 × 1/2" NPT - adaptors 2 × 3/4" NPT - adaptors 2 x M25x1.5mm - adaptors 1 × 1/2" NPT - adaptor 1 × 3/4" NPT - adaptor 1 x M25x1.5mm - adaptor
Stopping plug material: [m]	B N P S	Brass Nylon Nickel Plated Brass Stainless Steel
Duty label / Equipment tag: [d]:	1 2 3 4 5 6 7	No Duty label, no Equip. tag Duty label Stainless Steel Duty label St/St + Equip. tag Duty label Metalised Polyester Duty label M. Poly. + Equip. tag Equip. tag only Special label requirement
Product version: [v]A1		IECEX, ATEX, EAC, INMETRO, PESO approved
Enclosure colour: [x]	R B N Y V S K M Z	Red Blue Green Yellow Red/White Yellow/Black Black Magenta Red/Black
LED Indicator [u]	N L	No LED indicator required LED indicator required GNExCP6B version only - Default: N for A & C versions
Voltage: [v]	48, 24, 12, 6	System voltage in Vdc (only required for GNExCP6B or C type)
E.O.L.Module: [e] optional only for GNExCP6B or C type	ExxxR ED1 ExxxZ	Resistor value in Ohms e.g. E470R = 470 Ohm Diode IN4007 = ED1 Zener diode e.g. E5V1Z = 5.1V
Series Module: [s] optional only for GNExCP6B or C type	SxxxR SD1 SxxxZ	Resistor value in Ohms e.g. S1K5R = 1.5K Ohm Diode IN4007 = SD1 Zener diode e.g. S5V1Z = 5.1V
Spares:	SP70-0001 SP70-0040	Replacement break glass elements (Pack of 50) GNExCP6-BG Test Key
Accessories:	SP65-0001-A2 SP65-0001-A4 SP65-0002-A2 SP65-0002-A4 SP70-0065	Pole Mount Bracket Kit 2" St/St A2 (304) Pole Mount Bracket Kit 2" St/St A4 (316) Sunshade - St/St A2 (304) Sunshade - St/St A4 (316) Break glass hammer with chain

