

UCS(L)...

zone 1	zone 2	Ex de II	II2GD	-40°C	T4 (130°C)	-20°C	T6 (80°C)
zone 21	zone 22	Ex e [ia] IIC	II2(1)GD	+80°C		+40°C	
		Ex ia IIC	II2GD			-40°C	T5 (95°C)
			IP66			+60°C	

EMERGENCY PUSH-BUTTON WITH PROTECTION

PULSANTE DI EMERGENZA CON PROTEZIONE



Caratteristiche:	<p>Pulsante d'allarme antincendio UCS(L)...., con protezione ATEX (Exde).</p> <p>Modi di funzionamento da definire in sede di ordine:</p> <ul style="list-style-type: none"> - Pulsante di emergenza premi (ritorno a molla) - Pulsante di emergenza con aggancio sblocco a trazione - Pulsante di emergenza con aggancio sblocco a rotazione - Pulsante di emergenza con aggancio sgancio a chiave
Features:	<p>Fire alarm station UCS(L)...., with protection, ATEX (Exde).</p> <p>Modes of operation to be defined on order:</p> <ul style="list-style-type: none"> - Emergency push button push (spring return) - Stay put emergency push button pull to release - Stay put emergency push button rotating to release - Stay put emergency push button key released

Specifica tecnica - Technical specification

Materiale Material	<p>UCS(L)...A Alluminio - Aluminium LM6</p> <p>UCS(L)...G GRP glass fibre reinforced polyester</p> <p>UCS(L)...S Acc. Inox - Stainless steel 316</p>
Dimensioni Dimension	<p>UCS(L)...A 110x110x85mm (alternative dimension 170x110x85)</p> <p>UCS(L)...G 110x110x85mm (alternative dimension 170x110x85)</p> <p>UCS(L)...S 110x110x100mm (alternative dimension 200x100x100)</p>
Colore Color	<p>Rosso (altri a richiesta)</p> <p>Red (other on request)</p>
Imbocchi Cable entries	<p>1 gland M20 std execution</p> <p>on request:</p> <p>1 gland M25</p> <p>2 gland M20 or M25</p>

Contatti manuali Manual contact		Contatti manuali Manual contact		Contatti manuali Manual contact	
UCS(L)-21A	1 NO	UCS(L)-21G	1 NO	UCS(L)-21S	1 NO
UCS(L)-22A	1 NC	UCS(L)-22G	1 NC	UCS(L)-22S	1 NC
UCS(L)-25A	1 NC + 1 NO	UCS(L)-25G	1 NC + 1 NO	UCS(L)-25S	1 NC + 1 NO
UCS(L)-27A	2 NC	UCS(L)-27G	2 NC	UCS(L)-27S	2 NC
UCS(L)-29A	2 NO	UCS(L)-29G	2 NO	UCS(L)-29S	2 NO
UCS(L)-30A	1 NO + 2 NC	UCS(L)-30G	1 NO + 2 NC	UCS(L)-30S	1 NO + 2 NC
UCS(L)-31A	2 NC + 1 NO	UCS(L)-31G	2 NC + 1 NO	UCS(L)-31S	2 NC + 1 NO
UCS(L)-32A	3 NC	UCS(L)-32G	3 NC	UCS(L)-32S	3 NC
UCS(L)-33A	3 NO	UCS(L)-33G	3 NO	UCS(L)-33S	3 NO

Features of the Contact 10 A
Caratteristiche dei contatti 10 A

I_{th} = 10 A; U_i = 415 V

AC

U_e = 380 V; I_e = 1,9 A or
U_e = 240 V; I_e = 3 A or
U_e = 120 V; I_e = 6 A

DC

U_e = 250 V; I_e = 0,27 A or
U_e = 125 V; I_e = 0,55 A or
U_e = 24 V; I_e = 2,87 A



ALTRE ESECUZIONI SPECIALI A RICHIESTA
OTHER SPECIAL EXECUTION ON REQUEST

