

Mini Monitored Single Input Module


The Axis single input modules are loop powered, designed around a fully digital protocol and allow monitoring of fire alarm and auxiliary devices

The input channel is monitored and will detect Normal / Short / Alarm and Open conditions.

The unit provides fast alarm and fault signalling, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm².

The unit can be mounted within an electrical box or enclosure.



Standards and Approvals

- EN54-3:2001 +A1:2002 +A2:2006
- Approved by BRE/LPCB and certified by the UAE Civil Defence

Features

- Provides high reliability and error detection
- Short circuit isolators in each device to the requirements of EN54-17
- Large capacity, up to 240 devices per loop
- Auto addressing capability (by the control panel) or manually using a hand held programmer
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

Specification

Power Supply	15-40 V
Average Current Consumption	I=120 uA
LED Current Consumption	Iled=6mA @24Vdc
Operating Temperature Range	-30°C / +70°C
Humidity (non condensing)	95% RH
End-of-Line Resistor	(Reol): 27Kohm
Alarm resistor	(Rw): 10Kohm
Dimensions H x W x D mm	52 x 75 x 28 without brackets
Weight grams	180
IP Rating	21C

Order Codes and Options

20-VMMI100-ADV:	AV Mini Monitored Single Input Module
-----------------	---------------------------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.