

Intelligent Wall Sounder Interface module

The Intelligent Wall Sounder Interface Module is designed to allow the use of the Axis-CWS conventional sounders and Axis-CWSV conventional sounder beacon on an Axis EN intelligent loop.

The Axis-WSM module is compatible with intelligent control panels and systems based on the Axis EN protocol. Easy to install, it incorporates built-in short circuit loop isolation.

Once installed onto an Axis EN compatible intelligent loop, the device is fully addressable and benefits from an extensive range of intelligent control and monitoring functionality.



Dimensions

Features

- Flexible modular design
- Easy to install
- Manual and auto addressing options
- Built-in short circuit isolators
- Intelligent two-stage alarm capability
- Optional microphone self-test facility
- Addressing using the Device Programming Tool or Auto addressing capability via the fire control panel
- Fits Axis EN modular wall sounders and sounder beacons

Standards & Approvals

- EN54-17:2005 Short Circuit Isolators
- EN54-18:2005 Input / Output devices

Specifications

Power Supply voltage range	18 Vdc - 40 Vdc
Activated Circuit Load	(High Vol inc. Sounder) 5-8 mA at 24 Vdc
	(High Vol inc. Sounder Beacon) 11-25 mA at 24 Vdc
Operating Temperature Range	-25C to +70C
Weight Including Back Box	52 g
Max Tolerated humidity	95% RH (Non-condensing)
IP Rating	IP65

Order Codes and Options

Axis-WSM	Intelligent Wall Sounder Interface Module
Axis-CWS or Axis-CWS/W	Conventional Wall Sounder - Red or White
Axis-CWSV or Axis-CWSV/W	Conventional Wall Sounder Beacon - Red or White

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.