

Remote Indicator Unit

The remote indicator unit is used to give a remote indication of the status of a single or groups of fire detectors in alarm state utilising an LED with a wide area of illumination and high on/off contrast.

The units are compatible with the majority of conventional and addressable systems and can also be used for security and process control applications.

The standard version is a single gang flush mount unit, with or without 'Fire Detector Operated' text and also available with a deep back box for surface mounting.



Features

- Direct fit to a single gang deep back box
- Circular flush mounted version
- Available with text in other languages or without text
- Custom legend available on request
- IP66 weatherproof version available

Specification

Voltage range	5-28 Vdc
Nominal current consumption	24 mA
IP Rating	IP 24
Boxed weight	38 g (flush mount) 95 g (surface mount)
Colour	white (ABS fire retardant plastic)

Order Codes and Options

08-502-003	Remote Indicator Unit
08-502-001	Remote Indicator Unit without Text

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.