

Product data sheet uvex silv-Air 2220 FFP2 NR D with Carbon



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering cup shape mask with exhalation valve• Protection level FFP2• Soft material edges for high wearing comfort• Continuous head band for a comfortable and secure fit• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask• Flexible and adjustable nose clip• Compatible with uvex safety eyewear• Soft sealing lip guarantees a secure, comfortable sealed position of the mask• Activated carbon filter for odors, gases and vapors below limit value• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Nose clip: aluminum Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS
Weight	20 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8732.220	cup shape mask FFP2, white with valve and carbon	15 pcs. per box

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 10 times the respective limit values.	Woodworking, softwood, cement, metal, smog, fine dust, concrete, iron dust, ash, cotton dust, fluoride, carbon fibres, gypsum, fibre glass, copper, nickel, soot, pollen, house dust, pet hair.
--	---

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advice.