

Product data sheet uvex silv-Air 3310 FFP3 NR D



Product information

Product features	<ul style="list-style-type: none">• Particle-filtering flat fold mask with exhalation valve• Protection level FFP 3• Soft material edges for high wearing comfort• The adjustable head band offers an easy handling and comfortable fit• Exhalation valve reduces breathing resistance and build-up of heat and moisture in the mask• Flexible and adjustable nose clip• The masks are individually packed• Soft sealing lip guarantees a secure, comfortable sealed position of the mask• Compatible with uvex safety eyewear• Mask fulfils the requirements of the dolomite dust test (D)
Materials	Headband: textile Nose clip: PP Headband clips: PP Filter / mask: Melt Blown PP, Polyester Sealing lip: PVC foam Valve: ABS
Weight	15 g
Standard	EN 149:2001 + A1:2009

Versions

Article number	Colour/Version	Retail unit
8733.310	Flat fold mask FFP3, white with valve	15 pcs. per box
8753.310	Flat fold mask FFP3, white with valve	3 pcs. per bag
8753.311	Flat fold mask FFP3, white with valve	2 pcs. per bag

Areas of use*

The respiratory protection mask can be used against solid, aqueous and non-volatile liquid aerosols up to 30 times the respective limit values.	Woodworking, hard wood, chromium, asbestos (up to 100,000 F/m ²), stainless steel, lead, welding, dust that contain beryllium, arsenic, cadmium or cobalt. Medical waste disposal, fungal spores, legionella bacteria, infections, viruses, bacteria, enzyme, nanoparticles.
--	--

*Please note that the above mentioned areas of use are examples only. The selection of PPE needs to be carried out by a competent person, in conjunction with relevant and current legislation.

Uvex accepts no liability for any possible harm or damage which may result from this information. This data sheet does not replace a detailed risk assessment nor seeking specialist advise.