











HS CODE
56090090
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N° 2777/10963-01/E10-01
Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland



REF.	FA 30 503 15	FA 30 503 20
 LG. KG	1.5 m (connector included)	2 m (connector included)
	Max. 100 KG	
CE	EN 355:2002	
MAT.	 PA 11 mm Polyamide	
	45 mm	
		
	NO	
	1.16 KG	1.17 KG



Largeur de l'absorbeur d'énergie
 Width of the energy absorber
Ancho del absorbedor de energía
 Larghezza del assorbitore di energia
Breite des Falldämpfers



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement



Ouverture
 Gate opening
Apertura
 Apertura
Öffnung



Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten