

Designation :

Energy Absorbing Expandable Webbing Lanyard

- Energy Absorbing in webbing, width 44 mm, which reduces the impact of the fall to less than 6 kN
- 44 mm wide polyester expandable elasticated webbing lanyard.
- Loops protected by an abrasion resistant tubular webbing

Connector :

1 aluminium rebar hook, opening 60 mm and 1 aluminium snap hook opening 21 mm

Compliance :

EN355 : 2002

Length :

Expanded length : 2 m
Relaxed length : 1.4 m

Materials :

Lanyard : polyester
Absorber : polyester and polyamide
Connector : aluminium



HS code	Carton size / Pieces	Unit Weight
56090090	60x40x24 / 20	1.05 kg

Satra Technology Centre, N°0321
Wyndham Way, Telford Way, Kettering,
Northamptonshire, NN16 8SD, United Kingdom.

Article 11: GB07/73551

SGS United Kingdom Ltd., N° 0120
Unit 202B, Worle Parkway,
Weston-super-Mare, BS22 6WA, United Kingdom



MAJ : 11/14

ZI les portes du Dauphiné
4 rue de l'Aigue
69 780 St Pierre de Chandieu – France
Tel : +33 (0)4 72 48 78 27 Fax : + 33 (0)4 72 48 58 32
www.kratossafety.com info@kratossafety.com

